



IntelliHouse

5-16kWh Wall/Floor-Mounted Low-Voltage Energy Storage System (ESS)


Slim Wall/Floor -Mounted Storage
Durable & Space-Saving

- Uses A+ grade cells, $\geq 6,000+$ cycle life ^①
- Built-in emergency fire suppression with multi-layer safety protection
- Supports a maximum string input current of 21A, ensuring compatibility with high-power PV modules
- Supports 160% usable PV power, maximizing solar energy utilization
- Supports 200% overload in off-grid mode, ensuring stable startup of loads
- Supports seamless on-grid and off-grid switching with transfer times $< 10\text{ms}$
- Designed for all environments: IP66 protection & C5-M anti-corrosion. Optional intelligent heating enables operation down to -20°C
- Supports up to 8 units in parallel, expanding capacity up to 128kWh
- Solis AI – smart energy management with generator support
- Supports OTA remote upgrades for efficient operation and maintenance

IntelliHouse 10 kWh ESS



IntelliHouse 5kWh ESS



IntelliHouse 16 kWh ESS



DATASHEET

IntelliHouse-(5-16)kWh

Models	5kWh	10kWh	16kWh
Performance			
Battery type	LiFePO ₄		
Nominal energy	5 kWh	10 kWh	16 kWh
Operating voltage	44.8-57.6 V		
Cell capacity	100 Ah		314 Ah
Recommended charge & discharge current rate	0.5 C/0.5 C		
Max. charge & discharge current rate	0.5 C/1 C		0.5 C/0.5 C
Recommended charge & discharge current	50 A	100 A	157 A
Max. discharge current	100 A	200 A	157 A
Depth of discharge	> 95%		
Display	SOC indicator, Status indicator		
Communication	CAN/RS485		
Cycle life ^①	≥6000		
Protection			
Over/under voltage protection	Yes		
Over current protection	Yes		
Over/under temperature protection	Yes		
DC breaker	Yes		
Fire protection function	Yes		
General Specification			
Dimensions (W × H × D)	470 × 655 × 175 mm	470 × 1075 × 175 mm	470 × 950 × 264 mm
Weight	47 kg	90 kg	122 kg
Cooling	Natural convection		
Ingress protection	IP66		
Anti-corrosion class	C5M		
Operating ambient temperature range	0~55 °C / -20~55 °C (Smart heating function, optional)		
Storage temperature range	-10~45 °C		
Relative humidity range	5~95 %		
Max. operating altitude	4000 m		
Installation method	Floor standing / Wall-mounted		
Scalability	Up to 8 units in parallel		
Compatible inverters	S6-EH1P(3-6)K-L-EU, S5-EH1P(3-6)K-L(Smart), S6-EH1P(3-10)K-L-PLUS, S6-EH1P(9.9-18)K03-NV-YD-L, S6-EH2P(5-8)K02-SV-YD-L, S6-EH2P(9.6-16)K03-SV-YD-L-US, S6-EH3P(5-18)K02-NV-YD-L, S6-EH3P(7-10)K02-LV-YD-L, S6-EA1P(3.6-6)K-L, S6-EO1P(4-6)K-48, S6-EO1P(4-5)K-48-EU		
Standard Compliance			
Certificates	IEC 62619, IEC63056, UN 38.3, EN/IEC61000-6-1/2/3/4, RoHS, REACH		

① This is provided by the battery cell manufacturer. Defined with standard test condition: the battery is within 70%SOH, charge and discharge at a constant current (0.2C) and an ambient temperature at 25°C±2°C.