

DATASHEET

PrimePower-109kWh-50kW-NV

Models	109kWh-50kW
System	
Rated energy capacity	109.7 kWh
Max. cycle rate	0.5 P
Max. cycle efficiency ^①	89%
Usable energy capacity	98.7 kWh
Dimensions (W × H × D)	1270 × 2070 × 1357 mm
Dimensions (without inverter) (W × H × D)	950 × 2070 × 1357 mm
Weight	1320 kg (Cabinet) + 73 kg (Inverter)
Operating temperature range	-25 ~ +55°C
Storage temperature range	0 ~ 40°C
Operating humidity range	≤ 95% (non-condensing)
Max. operation altitude	4000 m
System temperature control mode	Industrial-grade air-conditioning (Cabinet); Natural cooling (Pack); Intelligent fan-cooling (Inverter)
Fire suppression mode	Default: Aerosol, Explosion relief valve, Fire water inlet Optional: Flammable gas detector, Explosion relief panel, Audible and visual alarm
Ingress protection	IP55 (Cabinet) + IP66 (Inverter)
Anti-corrosion class (Battery)	C4/C5 (Optional)
Anti-corrosion class (Inverter)	C5
Noise (rated operating condition)	70 dB(A) @ 1 m
Lightning protection	Type II (AC port), Type II (PV&Battery)
Protection mode	Anti-islanding protection, residual current detection, insulation resistance detection, AC overcurrent protection, and AC cable connection protection
Certification standards	IEC62619, IEC61000-6/2/4, IEC62040, IEC63056, IEC62477, UN38.3
Battery	
Cell type	LFP 3.2 V / 306 Ah
Cell cycle life ^②	10000
System battery configuration	1P112S
Rated voltage	358.4 V
Operating voltage range	313.6 ~ 403.2 V
Rated DC current	153 A
Number of battery packs	7
Battery pack capacity	15.67 kWh
Battery pack weight	102 kg
Inverter	
Inverter model	S6-EH3P50K-H(21A)
Rated output power	50 kW
Max. apparent output power@On-grid	50 kVA
Rated grid voltage	3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V
Rating grid frequency	50 Hz / 60 Hz
AC grid frequency range	45 - 55 Hz / 55 - 65 Hz
Rated output current	76 A / 72.2 A
Max. apparent output power@Off-grid	1.6 times of rated power, 2 s
Back-up switch time	< 10 ms
Power factor	> 0.99 (0.8 leading - 0.8 lagging)
THDi / THDv (@linear load)	< 2% / < 3%
Max. usable PV input power	100 kW
Recommended max. PV array size	100 kW
Max. input voltage	1000 V
Rated voltage	600 V
Start-up voltage	180 V
MPPT voltage range	150 - 850 V
Max. input current	4 × 42 A
Max. short circuit current	4 × 60 A
MPPT number / Max. input strings number	4 / 8
Communication	Inverter interface: CAN, RS485, LAN; Dongle interface: Wi-Fi+LAN (Default), Cellular (Optional)
Max. parallel quantity (off-grid)	10

① Rated operating condition: Based on cell test condition of 25±2°C, 0.5P charge and discharge rate, and the AC output voltage is 380 or 400 Vac.

② This is provided by the battery cell manufacturer. Based on cell test condition of 25±2°C, 0.5P charge and discharge rate and SOH=70%.