

DATASHEET

S6-EH1P(3-8)K-L-PLUS, S6-EH1P(9-10)K-L-PLUS(21A)

Models	3K	3.6K	5K	6K	8K	9K(21A)	10K(21A)	
Input DC (PV side)								
Recommended max. PV array size	6 kW	7.2 kW	10 kW	12 kW	16 kW	18 kW	20 kW	
Max. usable PV input power	4.8 kW	5.76 kW	8 kW	9.6 kW	12.8 kW	14.4 kW	16 kW	
Max. input voltage	500 V							
Rated voltage	330 V							
Start-up voltage	90 V							
MPPT voltage range	90 - 435 V							
Max. input current	16 A / 16 A				32 A / 32 A		42 A / 42 A	
Max. short circuit current	20 A / 20 A				40 A / 40 A		48 A / 48 A	
MPPT number / Max. input strings number	2 / 2				2 / 4			
Battery								
Battery module models	SolisStor-5/10kWh-L-WM-20-SE; SolisStor-5/10/16kWh-L-WM-20; SolisStor-5/10/16kWh-L-WM-66; SolisStor-(5-40)kWh-L-ST-66							
Number of battery modules	1 ~ 8							
Battery voltage range	40 - 60 V							
Battery type	Li-ion / Lead-acid							
Max. charge / discharge power	3 kW	3.6 kW	5 kW	6 kW	8 kW	9 kW	10 kW	
Max. charge / discharge current	70 A	80 A	112 A	135 A	190 A	200 A	210 A	
Communication	CAN / RS485							
Output AC (Grid side)								
Rated output power	3 kW	3.6 kW	5 kW	6 kW	8 kW	9 kW	10 kW	
Max. apparent output power	3 kVA	3.6 kVA	5 kVA	6 kVA	8 kVA	9 kVA	10 kVA	
Operation phase	L/N/PE							
Rated grid voltage	220 V / 230 V							
Rated grid frequency	50 Hz / 60 Hz							
Rated grid output current	13.7 A / 13.1 A	16.4 A / 15.7 A	22.8 A / 21.8 A	27.3 A / 26.1 A	36.4 A / 34.8 A	40.9 A / 39.1 A	45.5 A / 43.5 A	
Max. output current	13.7 A / 13.1 A	16.4 A / 15.7 A	22.8 A / 21.8 A	27.3 A / 26.1 A	36.4 A / 34.8 A	40.9 A / 39.1 A	45.5 A / 43.5 A	
Power factor	> 0.99 (0.8 leading - 0.8 lagging)							
THDi	< 3%							
Input AC (Grid side)								
Input voltage range	187 - 253 V							
Max. input current	21 A	25 A	32 A	40 A	50 A	60 A	65 A	
Frequency range	45 - 55 Hz / 55 - 65 Hz							
Output AC (Back-up)								
Rated output power	3 kW	3.6 kW	5 kW	6 kW	8 kW	9 kW	10 kW	
Max. apparent output power	2 times of rated power, 10 s							
Back-up switch time	< 10 ms							
Rated output voltage	L/N/PE, 220 V / 230 V							
Rated frequency	50 Hz / 60 Hz							
Rated output current	13.7 A / 13.1 A	16.4 A / 15.7 A	22.8 A / 21.8 A	27.3 A / 26.1 A	36.4 A / 34.8 A	40.9 A / 39.1 A	45.5 A / 43.5 A	
Max. AC passthrough current	35 A	35 A	40 A	40 A	50 A	60 A	65 A	
THDv (@linear load)	< 2%							
Input Generator								
Max. input power	3 kW	3.6 kW	5 kW	6 kW	8 kW	9 kW	10 kW	
Max. input current	13.7 A / 13.1 A	16.4 A / 15.7 A	22.8 A / 21.8 A	27.3 A / 26.1 A	36.4 A / 34.8 A	40.9 A / 39.1 A	45.5 A / 43.5 A	
Rated input frequency	50 Hz / 60 Hz							
Efficiency								
Max. efficiency	96.2%							
EU efficiency	96.1%							
BAT charged by PV / AC max. efficiency	95.3% / 93.9%							
BAT discharged to AC max. efficiency	93.8%							
Protection								
Anti-islanding protection	Yes							
Ground fault monitoring	Yes							
DC reverse-polarity protection	Yes							
Integrated AFCI 2.0	Optional							
Protection class / Over voltage category	I / II (PV and BAT), III (MAINS and BACKUP and GEN)							
General Data								
Dimensions (W × H × D)	335 × 560 × 253 mm							
Weight	23 kg		23.5 kg			23.8 kg		
Topology	High frequency isolation (for battery)							
Operating ambient temperature range	-25 ~ +60°C							
Relative humidity	0 - 100%							
Ingress protection	IP66							
Noise emission (typical)	< 65 dB(A)							
Cooling concept	Natural cooling				Intelligent fan-cooling			
Max. operation altitude	3000 m							
Grid connection standard	NRS 097-2-1, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, EN 50549-1, MEA, PEA, NBR 16149, NBR 16150, G98, G99, CEI 0-21, NTS 631 TypeA							
Safety / EMC standard	IEC/EN 62109-1/-2, EN 61000-6-2/-3							
Features								
DC connection	MC4 plug (PV port) / Terminal Block (BAT port)							
AC connection	Terminal Block							
Display	7.0" LCD display & Bluetooth + APP							
Communication	RS485, CAN, Optional: Wi-Fi, GPRS, LAN							